

# FOLDING HEAVY DUTY FLAIL SHREDDER STALK HAWK 7224F



- Optimal use in cotton, corn, rice and other crop residues
- 24 ft working width, hydraulically foldable

F.X.S. SAUERBURGER

**INNOVATIVE MACHINERY  
FROM GERMANY**

○ INNOVATION

○ PASSION

○ TRADITION

○ MADE IN GERMANY

# STALK HAWK 7224F

- Heavy-duty class
- Foldable
- Easy maintenance

## Dual drive

6 x belts on each side with automatic tensioning system. The belt housing is fan cooled.

## Heavy-duty gearbox

Heavy-duty gearbox with integrated over-running design

## Even load distribution on 3-point hitch

- Heavy built 3-point mount with cat 3/4N Quick Hitch compatible
- Horizontal pulling bar that spreads the load over the full width of the hitch

## Double chain shielding

Double chain shielding in the front

## Hydraulic transport lock

Automatic locking when folding and hydraulic unlocking when unfolding.

## Quick Hitch compatible

Quick Hitch Cat 3 and 4N compatible

## Inspection doors

Four easy-opening doors on the rear for maintenance

## Gauge wheels

- Four swiveling gauge wheels
- Adjustable row spacing
- Adjustable cutting height

Photo: STALK HAWK 7224F with European pneumatic tires

## Large rotor with long Y knives

Long Y-knives for a total rotor diameter of 28.5". Suction palets to increase product flow in the shredder are available in option.

## STANDARD EQUIPMENT

Large rotor with long Y-flail knives for cotton or corn • double chain shielding • automatic belt tensioning system • fan blades mounted on the v-belt pulley for better heat dissipation in the V-belt drive • over-running clutch integrated inside the gearbox – driveline shaft included • support frame with two hydraulic, folding mulching heads • Load distribution over the entire width of the 3-point hitch thanks to a specially developed support frame • bolt-on rear inspection doors • hydraulic transport lock • bolt-on heavy-duty skid shoes – four heavy-duty gauge wheels, adjustable in width and pivoting.

## OPTIONAL EQUIPMENT

Suction palet flails installed between the Y flails • driveline shaft 1 3/4", 20 splines instead of 1 3/8", 21 splines • full width rear roller



The STALK HAWK 7224F folds hydraulically for transport. When folding, both flail shredder heads lock mechanically and automatically. To unfold, the driver unlocks the system with a small hydraulic cylinder without stepping out of the tractor. In transport position, the swiveling gauge wheels automatically fall in position alongside the heavy-duty frame structure. This reduces the overall length to the rear.

The four rear inspection doors can be opened for maintenance and cleaning operations. Optionally, the shredder can be equipped with a double skin plate made of wear-resistant high grade steel. This plate is bolted on spacers inside the hood. The plate absorbs impact from thrown objects. This increases significantly the life of the shredder.

In the field, the gauge wheels can be adjusted in width and height to fit the row spacing and crop conditions.



While shredding, the load is equally spread on the full width of the implement hitch. A massive horizontal beam is integrated in the heavy-built 3-point system and the left and right shredder heads lock onto it when unfolding. Adjustable spacers allow an even more precise setup.

A massive center gearbox, with integrated over-running function, transfers the power to both end drives. Each end drive is made of six belts with an automatic tensioning system. The tension pulley presses the belts toward the center of the system. This increases the contact surface of the belts with the main drive pulleys.


The four gauge wheels are swiveling and can be adjusted in width to the row spacing. The height adjustment allows cutting heights up to 16" so the STALK HAWK can do a great job even on beds. Also optional for the shredder is a full width roller.

# STALK HAWK 7224F (24')

**SAUERBURGER**



Photo: STALK HAWK 7224F with European pneumatic tires



## TECHNICAL DATA

Order code	STALK HAWK 7224F 7158G
Mounting	Cat 3 / 4N Quick Hitch compatible
Working width (ft/m)	24' / 7.20 m
Transport width (ft/m)	9.5' / 2.90 m
Transport lock (autom./hydraulic)	standard equipment
Number of wheels	4
Tires - hub	280/70R15 - 6 bolts
Full width rollers	2 (one on each side) - optional
Cutting height	1 to 18"
PTO speed	1,000 rpm
Flail type	long Y-flails / with suction pallet flails in between the Y-flail knives (optional)
Number of flails	192
Rotor diameter (with flails)	28.5"
Rotor tube diameter	10" 3/4
Driveline protection	2 x 6 belts
Automatic belt tensioning system	standard equipment
Fan cooled belt housing	standard equipment
Side band thickness	4 ga. / 5 mm
Chain shielding	Double chain shielding front
Rotor bearing	2 3/4"
Weight (approx. lbs/kg)	9,150 lbs / 4,150 kg

All information and illustrations are approximate and non-binding. We reserve the right to make design changes at any time.

**SAUERBURGER**

TRAKTOREN UND GERÄTEBAU GMBH

Im Bürgerstock 3 | 79241 Wasenweiler | Germany  
info@sauerburger.de | www.sauerburger.us



Your manufacturers representative

**H HOOD & COMPANY, INC.**  
Agricultural Equipment

Springfield, MO  
Phone: (417) 865-2100

02.2025